

Laser Accessories



LS330 Laser Jamb Pole

The laser jamb pole is an ideal mounting platform for line generating or dot lasers when a tripod is not high enough to reach your required datum height.

The laser pole mounts between the floor and the ceiling and screws together in five sections with an adjustable elevating instrument platform.



LS306 Laser Glasses

The wearing laser glasses, helps to make the red laser line more visible to the operator when the ambient light conditions of the work site are not conducive for easy visibility (ie too bright). These are useful for all indoor trades using visible lasers.

LS304-2 Multi Function Mount

The multi function mount is a durable platform to easily mount a rotating laser level to a wall or ceiling track. This mount is ideal to position a laser at the desired height particularly when installing drop ceilings.



LS307 Magnetic Target

The magnetic target is used to enhance the brightness of a laser dot or line. There are two models available – grid mounted and floor mounted.



LS705 Laser Receiver

The LS705 receiver is used to detect the laser beam emitted from the laser and determine the height of laser plane. This detector can be used with most rotating lasers.



Laser accessories

LS330 features

- Adjustable elevating range 70 - 336cm
- Quick fix / release footplate mechanism
- Spring loaded end provides tight fit for sturdiness
- Five sections fit neatly into a handy carry bag

LS306 features

- Adjustable arm length for comfortable wearing

LS304-2 features

- Standard 5/8" screw bolt fits most laser levels
- A large hand wheel enables movement of the laser mounting platform up and down for fine alignment of the laser height through 150mm
- Mounting choices with the universal mount bracket. Either direct fix to wall or screw down onto the ceiling track

LS307 features

- The grid mounted target has inbuilt magnets for attaching to metal grid
- The floor mounted target has a back stand to keep the target upright on the floor
- The targets' measurement scale is in inches and centimetres

LS705 specifications

Precision	" +/- 3mm / 20m
Operation Range	250m Ø
Accuracy	
- coarse	+/- 2mm
- fine	+/- 1mm
Battery	2 x AA
Battery Life	360 hours
Clamp	Moveable quick clamp
Dimensions	150 x 76 x 29mm
Kit Weight	0.5kgs
Warranty	One Year