



LS604 / LS606 Multi Liner Lasers

These self leveling cross line lasers are a revolution in internal set out lasers. If you require horizontal, vertical and plumb visible reference lines then these lasers will make set out of your job site easy.

These ultimate set out tools project 4 or 6 laser beams simultaneously in the horizontal and vertical planes to form visible laser crosses and visible lines on your working area.

The extensive functions of these lasers provide convenience and productivity for all your interior and exterior set out applications. The LS604 and LS606 will do it all

Both lasers are supplied standard with a static laser line detection receiver which extends the operating range of the laser when being used indoors, and also makes the Lasers suitable for work outdoors in sunlight, for greater flexibility.

If you want to save hours in setting out time, forget 3-4-5 calculations, string lines and plumb bobs, these are the tools for you. You will say "Why didn't I get one of these years ago."

KIT INCLUDES

- LS604 / LS606 Laser
- Mini Tripod
- LS703 Detector
- LS603 Laser Glasses
- LS307 Magnetic Target
- Hard Padded Carry Case



LS604 features

- One horizontal line, two vertical laser lines at 90° to each other and a plumb down beam
- The above projections form three crosses at 90° to each other
- Plumb down beam can be adjusted for positioning over a central mark
- Rotating 360° Base with fine motion adjustment
- Tripod mounted or stand alone on the mini tripod supplied
- Heavy duty magnetically dampened compensator for fast self leveling
- Compensator locking switch for transporting
- Use with the LS703 detector (supplied) for extending the work range
- Out of level indicator - Laser Flashes and audible alarm
- Dustproof, Shower Proof and Anti Shock

LS606 features

- All of the features of the LS604 and
- Two horizontal lines, three vertical laser lines at 90° to each other and a plumb down beam
- The above projections form four laser crosses at 90° to each other

LS604 / LS606 specifications

Precision	" +/- 2mm / 10m
Self Leveling Range	" +/- 3.5°
Operation Range	
- without detector	15m – 20m Ø (light conditions dependent)
- with detector	80m Ø
Working Temperature	" -10°C to +45°C
Laser Diode	Class II 635nm
Power	Ni-MH rechargeable Battery Pack
Low Power Indication	Flashing power lamp
Battery Life	
LS604	15 hours
LS606	12 hours
Laser Dimensions	140mm x 125mm x 180mm
Kit Weight	4kg
Carry Case Dimensions	390mm x 300mm x 150mm
Warranty	One Year

www.theleveldepot.com.au

FREE CALL
1800 110 404

